

COAL RESOURCE OCCURRENCE AND COAL DEVELOPMENT POTENTIAL MAPS OF THE PINE BUTTE SCHOOL QUADRANGLE, BIG HORN COUNTY, MONTANA

> By W. C. CULBERTSON, L. N. ROBINSON AND T. M. GAFFKE 1978

PLATE 6 OVERBURDEN ISOPACH AND MINING-RATIO MAP OF THE ROLAND OF BAKER (1929) COAL BED

OPEN-FILE REPORT

PLATE 6 OF 64

EXPLANATION

in feet of overburden from surface to top of coal bed.

COAL--Drawn along the outcrop of the coal bed, the contact between burned and unburned

coal, and the fault boundary of the coal where the coal bed is 5 feet (1.5 m) or more thick; and the 5-foot (1.5 m) coal isopach. Arrows point toward area of Reserve Base

thickness of overburden, in feet, from surface to top of coal bed. Isopach interval

indicates cubic yards of over-

burden per short ton of recoverable coal by surface mining methods. Contours shown only within the strip-

for surface mining of the coal bed (in this quadrangle,

the 200-foot-overburden

isopach). Arrows point toward the area suitable for

multiply by 0.3. To convert cubic yards of overburden per short ton of recoverable coal to cubic meters of over-

burden per metric ton of recoverable coal, multiply

surface mining.

by 0.84.

coal.

200 feet.

ping limit.